#### REPT BATTERO

### тзілбянал

## JOIN THE GREEN JOURNEY



# **COMPANY**

#### >> Tsingshan Holding Group

Tsingshan Industry has invested in the new energy field by combining its rich mineral resources. Adhering to the mission of 'Refining a hundred years of stainless steel, building a green future', REPT BATTERO enjoys the unique resource integration ability and synergy advantage of the whole industrial chain conferred by Tsingshan Industry, and has become one of the fastest-growing battery producers in the industry.

#### N0.1

#### N0.1

Global stainless steel crude steel production output

Global nickel metal production output

N0.265

185000+

Total employees in 2025

Fortune Clobal 500 companies in 2024

#### >> Main Business

Supplying power battery systems and services for green transportation networks



Modules

Battery Packs

...



REPT BATTERO Energy Co., Ltd. was established in 2017. It is the first enterprise that Tsingshan Industrial has invested in the new - energy field. REPT BATTERO is mainly engaged in the research and development, production, and sales of lithium - ion batteries, and provides solutions for intelligent energy - storage systems.

The company has R&D centers in Shanghai, Wenzhou, and Jiaxing, as well as production bases in Wenzhou, Jiaxing, Liuzhou, Foshan, Chongqing, and Indonesia. Total production capacity in 2024 is 79GWh. It is expected that the capacity will exceed 90GWh in 2025. In the year of 2024, in terms of the shipment volume of energy - storage batteries, the company ranked fifth globally, and in terms of the shipment volume of batteries in the household energy - storage segment, it ranked second globally.

#### **BNEF** Tier1

BloombergNEF Tier 1 Energy Storage Manufacturers \$ 2.5 Billion

Sales revenue in 2024

NO.2

Clobal Household Energy Storage Battery Shipments in 2024 Global Energy Storage Battery Shipments in 2024

**NO.5** 

Supplying solutions and services for clean energy storage



#### >> Manufacturing Plant



WENZHOU, CHINA



JIAXING, CHINA



LIUZHOU, CHINA





CHONGQING, CHINA



MALUKU, INDONESIA

FOSHAN, CHINA

#### >> Energy Storage Cells

#### Ultility and C&I

	ETT	MET CON	Effect	STILLEP STAN	SBTAN
Capacity	280Ah	314Ah	314Pro	392Ah	587Ah
Nominal Voltage	3.2V	3.2V	3.2V	3.2V	3.2V
Voltage Range	2.50-3.65V	2.50-3.65V	2.50-3.65V	2.50-3.65V	2.50-3.65V
Cycle life	10000cycles	10000cycles	14000cycles	12000cycles	10000cycles
Dimension	71x173x207(mm)	71x173x207(mm)	71x173x207(mm)	<b>75</b> x182x224(mm)	73x275x218(mm)
Mass	5.48±0.15(kg)	5.60±0.15(kg)	5.70±0.15(kg)	6.82±0.15(kg)	9.9±0.30(kg)
Certificate	UL1973,UL9540A,IEC6 2619,UN38.3,UL1642, CB/T 36276	UL1973,UL9540A,IEC62619,UN3 8.3,UL1642,CB/T 36276,CB44240-2024,JIS C8715-2:2024,IEC62620	UL1973,UL9540A,IEC62619,U N38.3,UL1642,CB/T 36276,CB44240-2024,JIS C8715-2:2024,IEC62620	UL1973,UL9540A,IEC6261 9,UN38.3,UL1642,CB/T 36276,CB44240-2024	UL1973,UL9540A,IEC626 19,UN38.3,UL1642,CB/T 36276,CB44240-2024

#### **Residential** -

	LEP SOAN	anter a state	Effective Contraction of the second s	EL LEP 100C	LEP AND
Capacity	50Ah	72Ah	100Ah	100Ah	100Ah
Nominal Voltage	3.2V	3.2V	3.2V	3.2V	3.2V
Voltage Range	2.50-3.65V	2.50-3.65V	2.50-3.65V	2.50-3.65V	2.50-3.65V
Cycle life	7000cycles	6000cycles	6000cycles	3500cycles	5000cycles
Dimension	39x148x101(mm)	39x148x111(mm)	52x148x119(mm)	52x148x119(mm)	27x173x207(mm)
Mass	1.13±0.10(kg)	1.40±0.10(kg)	1.91±0.10(kg)	1.87±0.10(kg)	2.05±0.15(kg)
Certificate	UL9540A,UL1973,IEC62619,SII, JIS8715-2,UL1642,UN38.3	UL9540A,UL1973, IEC62619,UN38.3	UL9540A,UL1973,IEC62619, UN38.3,JIS8715-2	UL9540A,UL1973, IEC62619,UN38.3	UL9540A,UL1973, IEC62619,UN38.3

#### >>> Energy Storage System Product Matrix

	Y52 Module	Y104 Module	C&I All-in-One Cabinet	Battery Cabinet
Grouped Configuration	1P52S	1P104S	1P260S	1P416S
Nominal Voltage	166.4Vdc	332.8Vdc	400Vac, 3L/N/PE	1331.2Vdc
Voltage Range	130~189.8(Vdc)	260V~379.6(Vdc)	676-936(Vdc)	1081.6~1497.6(Vdc)
Nominal Energy	46.6kWh	104.5kWh	261.2kWh	372.7kWh
Dimension	1120×810×238(mm)	2150.5×779×250(mm)	1050×2250×1400(mm)	1300×1300×2230(mm)
Mass	330kg	690kg	2.58t	3. 5t



	Powtrix-i(BV) All-in-One ESS	Powtrix 1.0 DC Container	Powtrix 2.0 DC Container	Powtrix 3.0 DC Container
Grouped Configuration	416S10P	416S10P	416S12P	416S12P
Nominal Voltage	DC 1331.2V AC 690V	1331.2V	1331.2V	1331.2V
Battery Voltage Range	1040V~1500V	1040V~1500V	1040V~1500V	1040V~1500V
Nominal Energy	2.09MW, 4.18MWh	3.727MWh	5.016MWh	6.262MWh
Dimension	10080x2440x2940(mm)	6058×2438×2896(mm)	6058×2438×2896(mm)	6058×2438×2896(mm)
Nominal Mass	44.9t	36t	44.5t	49t

#### >> Energy Storage Project Highlight



Morowali Industrial Park (IMIP),Indonesia 150 MWh



California, USA 117.5 MWh



Texas, USA 226 MWh

Texas, USA 130 MWh



Chongqing, China 400 MWh



New South Wales, Australia 1,680 MWh



Ningxia, China 400 MWh



Ningxia, China 200 MWh



Xinjiang, China

800 MWh

Sofia Bulgaria 7.45 MWh



Ningxia, China 300 MWh



Trazhitsa, Bulgaria 7.45 MWh

#### >> ESG Management

Ø,	Supply Chain Traceability Management	01
	Energy Utilization	02
0	Battery Recycling	03
٥	Waste Emissions and Utilization	04
8	Employee Production Safety and Health	05
	Corporate Social Responsibility System	06





We will establish a development system aligned with the United Nations Sustainable Development Goals, creating a safe and healthy workplace for all employees and a green, eco-friendly community environment to ensure sustainable and rapid growth.

#### >> Global Industrial Layout

